

WAAS CH 82399 W33A	APP CRS 333°	Rwy Idg TDZE Apt Elev	9803 995 1015
--	------------------------	-----------------------------	--

RNAV (GPS) RWY 33
ROBERT GRAY AAF (GRK)

RNP APCH - GPS.



For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. Circling NA west of Rwy 15-33.
For inop ALS, increase LPV Cat E visibility to ¾ SM, LNAV/VNAV Cat E visibility to 2 SM, and LNAV Cat E visibility to 1½ SM.

MALSR



MISSED APPROACH: Climb to 3000 direct FIXUL and on track 283° to AGJ VORTAC and hold.

ATIS 124.9	GRAY APP CON 120.075 323.15	GRAY TOWER 120.75(CTAF) 285.5	GND CON 121.8 279.5	CLNC DEL 126.2 251.1
----------------------	---------------------------------------	---	-------------------------------	--------------------------------



3000 ↑	FIXUL ✱	tr 283° ◡	AGJ ◡	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 50).	
*LNAV only.				TIXFO	
RW33				RUBUF	3000
*1.5 NM to RW33				2600	333°
1.5 NM				3.4 NM	6.1 NM
CATEGORY				A	B
LPV	DA	1195-1/2 200 (200-1/2)			
LNAV/ VNAV	DA	1552-1 1/2 557 (600-1 1/2)			
LNAV	MDA	1460-1/2	465 (500-1/2)	1460-1 465 (500-1)	
CIRCLING		1540-1	525 (600-1)	1560-1 1/2 545 (600-1 1/2)	1620-2 605 (700-2) 1740-2 1/2 725 (800-2 1/2)