

RADAR MINS

23362

N1

RADAR INSTRUMENT APPROACH MINIMUMS

ALBEMARLE, NC
STANLY COUNTY (VUJ)
 RADAR-1 128.325 307.8 

Orig-A, 02NOV23 (23306) (FAA)

ELEV 609

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
PAR	22L	3.0°/40/887	ABCD	916-1	332	(400-1)

Rwy 22L helicopter visibility reduction below 3/4 SM not authorized.
 Procedure NA when control tower closed.

BEAUFORT, SC
BEAUFORT EXEC (ARW)
 RADAR-1 125.125 292.125  NA

Amdt 3B, 14JUL22 (22195) (FAA)

ELEV 9

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	25		ABC	440-1¼	430	(500-1¼)				
CIRCLING	ALL RWY		AB	500-1¼	491	(500-1¼)	C	640-1¼	631	(700-1¼)

Use Beaufort MCAS/Merritt Field altimeter setting.
 When Beaufort Class D not in effect, procedure NA.

22 FEB 2024 to 21 MAR 2024

22 FEB 2024 to 21 MAR 2024

SE-2

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

23362

N1

RADAR INSTRUMENT APPROACH MINIMUMS

BEAUFORT MCAS (MERRITT FLD) (KNBC), Beaufort, SC

Amdt 6 15JUL21 (21224) (USN)

ELEV 37

RADAR - (E) 123.7x 298.875x 317.775x 323.275x 338.35x 372.0x 379.275x **▽**

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
PAR ¹	5 ^{2 8}	3.0°/38/780	ABCDE	137-¼	100	(100-¼)
	23 ^{2 9}	3.0°/44/837	ABCDE	116-¼	100	(100-¼)
	14 ³	3.0°/41/777	ABCDE	233-¾	200	(200-¾)
	32 ⁴	3.0°/40/764	ABCDE	308-⅞	283	(300-⅞)
PAR W/O GS ¹	23 ^{5 6}		AB	360-½	344	(400-½)
			CDE	360-⅝	344	(400-⅝)
	14 ⁶		AB	420-1	387	(400-1)
			CDE	420-1½	387	(400-1½)
	5 ⁷		AB	440-¾	403	(500-¾)
			CDE	440-1	403	(500-1)
	32 ⁶		AB	440-1	415	(500-1)
			CDE	440-1½	415	(500-1½)
			AB	360-½	344	(400-½)
			CDE	360-⅝	344	(400-⅝)
ASR ¹⁶	14		AB	420-1	387	(400-1)
			CDE	420-1½	387	(400-1½)
			AB	440-¾	403	(500-¾)
	5 ⁷		CDE	440-1	403	(500-1)
			AB	500-1	475	(500-1)
	32		CDE	500-1½	475	(500-1½)
			AB	500-1	463	(500-1)
			C	580-1½	543	(600-1½)
CIR	5, 14, 23, 32		D	600-2	563	(600-2)
			E	740-2½	703	(800-2½)

22 FEB 2024 to 21 MAR 2024

22 FEB 2024 to 21 MAR 2024

¹No-NOTAM MP 1200-2000Z++ Sat.

²When ALS inop, increase vis to ½ mile.

³WCH for Group 4 is 16ft.

⁴WCH for Group 4 is 15ft.

⁵When ALS inop, increase vis to 1 mile.

⁶VDA and VGSI not coincident.

⁷When ALS inop, increase vis CAT AB to 1 mile, CAT CDE to 1½ miles.

⁸WCH for Group 3 is 18ft, Group 4 is 13ft.

⁹WCH for Group 4 is 19ft.

CODED LOST COMMUNICATIONS

SCARLET

TACAN equipped aircraft: If no transmissions are received for one minute in the pattern or 5/15 seconds on final approach, attempt contact with Beaufort Tower on 342.875/119.05 and proceed VFR. If unable, climb and maintain two thousand six hundred, proceed direct COSAW, execute TACAN Rwy 23 approach.

GOLD

RNAV/GPS equipped aircraft: If no transmissions are received for one minute in the pattern or 5/15 seconds on final approach, attempt contact with Beaufort Tower on 342.875/119.05 and proceed VFR. If unable, climb and maintain two thousand eight hundred, proceed direct HOWEL and execute RNAV/GPS Rwy 23 approach.

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

CHERRY POINT MCAS (CUNNINGHAM FLD) (KNKT), Cherry Point, NC

Amdt 5 02NOV23 (23306) (USN)

ELEV 29

RADAR - (E) 118.35x 120.15x 275.6x 299.6x 305.2x 314.8x 320.4x 337.2x 348.0x **T**

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATH/ HAA</u>	<u>CEIL-VIS</u>
PAR	32L ^{1 2}	3.0°/50/926	ABCDE	125-¼	100	(100-¼)
	5R ³	3.0°/55/1022	ABCDE	126-½	100	(100-½)
	14L ⁴	3.0°/55/1050	ABCDE	126-½	100	(100-½)
	23R ⁵	3.0°/56/1066	ABCDE	123-½	100	(100-½)
ASR	23R ⁶		AB	400-½	377	(400-½)
			CDE	400-¾	377	(400-¾)
	32L ^{2 6}		AB	400-½	375	(400-½)
			CDE	400-¾	375	(400-¾)
	5R ³		AB	500-1	474	(500-1)
			CDE	500-1¾	474	(500-1¾)
	14L ⁴		AB	500-1	474	(500-1)
			CDE	500-1¾	474	(500-1¾)
C CIR	All Rwys		AB	580-1	551	(600-1)
			C	580-1½	551	(600-1½)
			D	580-2	551	(600-2)
			E	700-2½	671	(700-2½)

¹When ALS inop, increase vis to ½ mile.

²VGSI and descent angle/PAR glidepath not coincident (VGSI Angle 3.00/TCH 78).

³VGSI and descent angle/PAR glidepath not coincident (VGSI Angle 3.00/TCH 73).

⁴VGSI and descent angle/PAR glidepath not coincident (VGSI Angle 3.00/TCH 71).

⁵CAUTION: PAR RPI and PAPI RRP not coincident.

⁶When ALS inop, increase vis to 1 mile.

22 FEB 2024 to 21 MAR 2024

22 FEB 2024 to 21 MAR 2024

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

NEW RIVER MCAS (MC CUTCHEON FLD) (KNCA), Jacksonville, NC

Amdt 2 22APR21 (23362) (USN)

ELEV 26

RADAR - (U) 118.575 132.2 279.575 289.4 308.4 346.325 350.225 353.875

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATH/ HAA</u>	<u>CEIL-VIS</u>
PAR	1 ¹	3.0°/45/871	ABCD	124 -¼	100	(100-¼)
	5 ⁵	3.0°/35/650	ABCD	126 -½	100	(100-½)
	19 ⁹	3.0°/41/760	ABCD	123 -½	100	(100-½)
	23 ⁴	3.0°/36/656	ABCD	274 -¾	250	(300-¾)
PAR W/O GS	1 ²		AB	420 -¾	396	(400-¾)
			CD	420 -¾	396	(400-¾)
	5 ¹⁰		ABCD	400 -1	374	(400-1)
	19 ¹¹		ABCD	400 -1	377	(400-1)
	23 ⁹		AB	440 -1	416	(500-1)
CD			440 -1½	416	(500-1½)	
ASR	5 ^{6 12}		AB	420 -1	394	(400-1)
			CD	420 -1½	394	(400-1½)
	23 ⁸		ABCD	380 -1	356	(400-1)
			AB	480 -1	457	(500-1)
19 ⁷		CD	480 -1½	457	(500-1½)	
		CIR	ALL RWY	AB	500 -1	474
C	500 -1½			474	(500-1½)	
D	580 -2			554	(600-2)	

22 FEB 2024 to 21 MAR 2024

22 FEB 2024 to 21 MAR 2024

¹When ALS inop, increase vis to ½ mile.

²When ALS inop, increase CAT AB vis to 1 mile, CAT CD vis to 1½ miles. The difference between the VGSI TCH (45 ft) and the procedure TCH (49 ft) is greater than 3 ft.

³CAUTION: WCH for aircraft similar to B-1, B-747, C-5, KC-10 is 16 ft.

⁴CAUTION: WCH for aircraft similar to B-727, C-141, P-3 is 16 ft and aircraft similar to B-1, B-747, C-5, KC-10 is 11 ft less than min 20 ft.

⁵CAUTION: WCH for aircraft similar to B-747, C-141, P-3 is 15 ft and aircraft similar to B-1, B-747, C-5, KC-10 is 10 ft less than min 20 ft.

⁶Step Down Fix 2 NM from thld, 600 min.

⁷Step Down Fix 2 NM from thld, 700 min.

⁸Step Down Fix 2 NM from thld, 620 min.

⁹Step Down Fix 3 NM from RPI, 900 min.

¹⁰Step Down Fix 2 NM from RPI, 540 min.

¹¹Step Down Fix 2 NM from RPI, 760 min.

¹²VGSI and descent angle not coincident.

RADAR INSTRUMENT APPROACH MINIMUMS