


WAAS CH 93719 W36A	APP CRS 357°	Rwy Idg TDZE 25 Apt Elev 25	9503
--	------------------------	---	-------------

RNAV (GPS) RWY 36

MYRTLE BEACH INTL (MYR)

RNP APCH.		MALSF	MISSED APPROACH: Climb to 2000 direct UXDEP and hold.	
▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. ▲ Inop table does not apply to LPV. For inop ALS, increase LNAV/VNAV Cats D/E visibility to RVR 6000, and LNAV Cats C/D/E visibility to 1½ SM.		✎		

ATIS 123.925	MYRTLE BEACH APP CON ★ (171° - 321°) 127.4 257.95 (322° - 170°) 119.2 350.3	MYRTLE BEACH TOWER ★ 128.45 (CTAF) 0 259.3	GND CON 120.3 275.8	CLNC DEL 120.3	UNICOM 122.95
------------------------	---	---	-------------------------------	--------------------------	-------------------------



2000	UXDEP	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).			
*LNAV only.		PORKE			
*1.2 NM to RW36		CHACA			
1600		1600			
GP 3.00°		TCH 52			
1.2 NM		3.6 NM		6 NM	
CATEGORY	A	B	C	D	E
LPV DA	225/40		200 (200-¾)		
LNAV/VNAV DA	374/45		349 (400-⅞)		
LNAV MDA	480/40		455 (500-¾)		480/50 455 (500-1)
CIRCLING	560-1 535 (600-1)		740-2 715 (800-2)	740-2¼ 715 (800-2¼)	740-2½ 715 (800-2½)

