

WAAS CH 56529 W07A	APP CRS 067°	Rwy Idg TDZE 3490 Apt Elev 3490
--	------------------------	---

RNAV (GPS) RWY 7

ROUNDUP (RPX)

▼

▲ NA

Use Billings altimeter setting, when not received, procedure NA.
When VGSi inop, Straight-in/Circling Rwy 7 procedure NA at night.
DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA.

MISSED APPROACH: Climb to 6300 direct PULAE and hold.

BIL ASOS 126.3	SALT LAKE CENTER 126.85 305.2	UNICOM 122.8 (CTAF)	122.7 0
--------------------------	---	-------------------------------	----------------

7 NM Holding Pattern		SWIVL		VGSI and descent angles not coincident (VGSI Angle 4.00/TCH 43).		6300	PULAE		
6600		BAYAM		KENPE 2.5 NM to RW07		RW07			
7.5 NM		2.7 NM		2.5 NM					
CATEGORY	A	B	C	D					
LP MDA	3940-1	450 (500-1)	3940-1 $\frac{3}{8}$	450 (500-1 $\frac{3}{8}$)					
LNAV MDA	3960-1	470 (500-1)	3960-1 $\frac{3}{8}$	470 (500-1 $\frac{3}{8}$)					
CIRCLING	4000-1	510 (600-1)	4140-1 $\frac{3}{4}$ 650 (700-1 $\frac{3}{4}$)	4340-2 $\frac{3}{4}$ 850 (900-2 $\frac{3}{4}$)					

ELEV 3490

TDZE 3490

6300

PULAE

067° to RW07

2440 X 100

5099 X 75

34

MIRL Rwy 7-25 0

ROUNDUP, MONTANA
Orig-B 14JUL22

46°29'N-108°33'W

ROUNDUP (RPX)

RNAV (GPS) RWY 7